

# **Telpower Specialty Fuses**

# 75 Type

#### **Specifications**

**Description:** Cylindrical with leads, designed to provide protection against

currents resulting from the application of foreign voltages.

Application for data sets and telephones. Dimensions: See Dimensions illustration.

Ratings:


Volts: - 135Vac/220Vdc (440Vdc@0.007A)

Amps: - 0.007-0.230A Agency Information: CE

## **Catalog Numbers**

Catalog Numbers	Amp Rating	Lucent Comcode Ref. No.	Code/ List No.
75C	0.007	103260816	KS23825-L3
75F	0.063	104172861	KS23825-L6
75B	0.115	102732112	KS23825-L2
75D	0.129	104013180	KS23825-L4
75A	0.200	102660008	KS23825-L1
75E	0.230	104015292	KS23825-L5

### Dimensions - in (mm)



# 76 Type

#### **Specifications**

**Description:** Cylindrical with leads, designed to provide protection against currents resulting from the application of foreign voltages. Application for data

sets and telephones.

**Dimensions:** See Dimensions illustration.


#### Ratings:

Volts: - 135Vac/440Vdc Amps: - 0.012-0.412A Agency Information: CE

## **Catalog Numbers**

Catalog Numbers	Amp Rating	Lucent Comcode Ref. No.	Code/ List No.
76D	0,012	103798245	KS23825-L10
76B	0.191	102965688	KS23825-L8
76A	0.231	102810181	KS23825-L7
76C	0.412	103656625	KS23825-L9

#### Dimensions - in (mm)



# 80 Type

#### **Specifications**

Description: A fuse designed for high reliability applications where high ambient temperatures, low circuit voltages, low power dissipation and low contact resistance are prime considerations. The 80 Type is a visual indicating fuse with remote electrical alarm capability. UL Recognized, Guide JDYX2, File E19180.

**Dimensions**: See Dimensions illustrations.

Ratings:


Volts: - 160Vdc

Agency Information: CE, UL Recognized File E19180.

#### **Catalog Numbers**

Catalog Numbers	Amp Rating	Color Code	Lucent Comcode Ref. No.	Code/ List No.
80G-½	1/2	Red	103839916	KS23824-L6
80M-1-1/3	11%	White	408078657	KS23824-L8
80B-2	2	Orange	103752150	KS23824-L2
80C-3	3	Blue	103752168	KS23824-L3
80D-5	5	Green	103800637	KS23824-L4

#### Dimensions - in (mm)



## 81 Type

#### **Specifications**

Description: Cylindrical, fast-acting, non-indicating high current companion to the 80 Type.

**Dimensions**: See Dimensions illustration.

Ratings:

Volts: - 65Vdc Amps: - 7 ½-12A

Agency Information: CE, UL Recognized, Guide JDYX2,

File E19180.

#### **Catalog Numbers**

Catalog Numbers	Amp Rating	Color Code	Lucent Comcode Ref. No.	Code/ List No.
81B-7-½	7 ½	Gray	103828141	KS23824-L12
81A-10	10	Yellow	103752176	KS23824-L11
81C-12	12	Lt Blue	104391842	KS23824-L13

#### Dimensions - in (mm)

